



#### USA

#### **MACHINE PRICES AND SPECIFICATIONS**

Effective January 1, 2022



## FX-520 Rotary Cutter



#### **SPECIFICATIONS**

- Overall Width --- 247" (6.2m)
- Overall Length --- 242" (6.15m)
- Cutting Height 2" 17.5" (Depending on Tire Size)
- Cutting Width --- 240" (6.10m)
- Transport Width --- 91" (2.32m)
- Transport Height --- 120" (3.05m)
- Cutting Capacity --- 2" (51mm)
- 2" (51mm) Fixed Knife 4" (102 mm) Pan Unit
- Min. Tractor Size --- 100hp (75kw)
- Blade Tip Speed --- 16,000 ft/min
- Blade Overlap --- 6" (153mm)
- Deck Thickness 180" (7 ga) (4.6mm)

	~ ~ Selection 1 ~ Choose a Basic Unit ~ ~					
				Price	e USA	Wt/lbs
1)	C520-100	Basic 20' Unit, 1000 RP	M		46,985.00	5,221
2)	S000-080	Safety Light Kit (Require	ed)		553.00	
		~ ~ Selection 2 ~	Choose a Hitch Type and Access	ories ~ ~		
2)	C520-800	Trailing hitch, CV Style			1,330.00	179
	Choose	e a Clevis:				
	a)	C000-513WG	Solid Tongue		466.00	13
	b)	C000-507WG	Open Clevis		420.00	12
	c)	C000-500WG	Precision hitch		741.00	29
	d)	C000-516WG	Solid Tongue with 2-3/16" hole for 2" pin		383.00	
	e)	C000-515WG	Clevis with 2 3/16" Opening		526.00	13
	f)	C000-510WG	Pro Level Hitch		578.00	
	Choose	e a Tractor Shaft:				
	a)	340-8082WG	CV Shaft, 1 3/4 x 20 Spline		2,216.00	79
	b)	340-8092WG	CV Shaft, 1 3/8" x 21 Spline		2,216.00	79
3)	C520-180	Parallel Ring hitch (For	European Applications Only)		1,830.00	217
	a)	340-5515WG	Shaft, 1 3/8" x 6 with Over-Running Clutch		1,716.00	79
4)	C520-175	High hitch (For Germa	ny Only)		2,144.00	262
	Choos	e a Tractor Shaft:				
	a)	340-8092WG	CV Shaft, 1 3/8" x 21 Spline		2,216.00	79
	b)	340-8082WG	CV Shaft, 1 3/4" x 20 Spline		2,216.00	79
		Assem	bly charge on pan units	Net	550.00	
		Assem	bly charge on fixed blade units	Net	650.00	



This list supersedes all previous lists.



## **USA**

## MACHINE PRICES AND SPECIFICATIONS





## FX-520 Rotary Cutter

			Price USA	Wt/lbs
		~ ~ Selection 3 ~ Choose a Blade Configuration ~ ~		
1)	C520-250	Pan Kit with Updraft Blades and Shrouds	3,972.00	624
2)	C520-260	Pan Kit with Shredder Blades and Shrouds	4,572.00	761
3)	C520-265	Fixed Knife Shredder Kit with Updraft Blades & Shrouds	6,855.00	965
4)	C520-295	Fixed Knife Kit with Flat Blades & Shrouds (For Cotton)	6,630.00	981
	~~	Selection 4 ~ Choose a Safety Guard and Accessories	~~	
1)	C520-500 a)	Single chains front and rear C520-580 Half Length Front Belting (Must be used with a chain option)	1,826.00 391.00	340 31
2)	C520-550 a)	Double chains front and rear C520-580 Half Length Front Belting (Must be used with a chain option)	2,560.00 391.00	677 31
		~ ~ Selection 5 ~ Choose Axle Option ~ ~		
1)	C520-612	Standard 618 Axle kit (Choose 4 Tires)	4,732.00	
2)	C520-614	517 Axle Kit c/w Center duals (choose 6 Tires)	4,785.00	
3)	C520-616	517 Axle Kit c/w Center Walking (choose 6 Tires)	5,349.00	
4)	C520-618	517 Dual Axle Kit (Choose 8 Tires)	5,440.00	
5)	C520-622	517 Walking Axle kit (Choose 8 Tires)	6,493.00	
6)	C520-624	517 Center Walking Axle c/w Duals on Wings (Choose 8 TireS)	5,922.00	
		~ ~ Selection 6 ~ Choose Tire Option ~ ~		
7)	210-560WG	Tire Assembly Stubble Proof (Choose quanity of tires needed 6 or 8)	600.00	
8)	210-182WG	Aircraft Tire (Choose quanity of tires needed 6 or 8)	453.00	
9)	210-182FWG	Foam Filled Aircraft Tire (Choose quanity of tires needed 6 or 8)	675.00	
10)	210-505WG	Light Truck Tire (Choose quanity of tires needed 6 or 8)	326.00	



This list supersedes all previous lists.



USA

**MACHINE PRICES AND SPECIFICATIONS** 



## FX-520 Rotary Cutter

Selection 7 ~ Choose a Destination Code

Effective January 1, 2022
Price USA Wt/lbs

80.00 475.00 (Estimate)	North America and Australia Destination Kit  Foreign Destination Kit (Amount may vary depending on country)			
	~ ~ Selection 8 ~ Schulte Fan Kit ~ ~			
10,158.00	Fan Debris Kit, <i>Factory Installed</i>	C520-780	.)	
9,972.00	Fan Debris Kit, <i>Crated</i>	C520-790	,	

**C Selection 9 ~ Extra Options ~ ~**C520-920 Crop Dividers 316.00 35

IMPORTANT: OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown Object Shield Information Message in the Rotary Cutter Spec Section in the sales price book.



This list supersedes all previous lists.

USA

#### MACHINE PRICES AND SPECIFICATIONS

Effective January 1, 2022



#### **FX-318 Pan Unit ROTARY CUTTER**

#### **CUTTER FEATURES**

- 540/1000 RPM 80° CV Drive
- 540 Equal angle non cv drive
- 7 ga Single Domed Deck and Stump Jumpers
- Rubber 3 Puck Grommet Suspension
- 90 HP Recommended Tractor
- Cutting Width 216" (5.5m)

- Replaceable Skid Shoes
- Height Control Cylinder & Hoses
- Wing Lift Cylinders & Hoses
- 1.75" to 16.75" (44.5mm to 425mm) Cutting Height
- Over Center Folding Wings
- Transport Width (max with duals on wings) 96"(2.4m)

## ~ ~ Selection 1 ~ Choose a Basic Unit, Drive Package ~ ~

			Price USA	WT(lbs)	
C318-100	Schulte FX-3	18, Basic Unit	22,162.00	5,593	
S000-085	Safety Light	Kit (Required)	585.00	30	
Choose a Driv	e Package:				
a)	C318-735	Drive Package, CW Center, 540 RPM	6,290.00	in base	
b)	C318-720	Drive Package, CW Center, 1000 RPM	6,290.00	in base	
~ ~ Selection 2 Trailing Hitch ~ ~					
Note: If usin	Note: If using Equal Angle Hitch Skip to Selection 3				
C185-180 Trailing Hitch, CV Style Required				204	
Choose a CV Shaft:					
a)	340-870WG	CV Shaft, 540 RPM	1,453.00	74	
b)	340-648WG	CV Shaft,44E tractor Shaft 1-3/8 Z21 - 1000 RPM	1,188.00	60	
c)	340-658WG	CV Shaft,44E tractor Shaft 1-3/4 Z20 - 1000 RPM	1,630.00	60	
Choose a C	levis:				
C000-506WG	Open Clevis	(Minimum Requirments)	428.00	11	
C000-500WG	Precision hit	ch	741.00	28	
C000-513WG	Solid Tongue		466.00	13	
C000-510WG	Pro Level Hi	ch	578.00		
	4	~ ~ Selection 3 ~ Equal Angle Hitch ~ ~			
C185-196	Equal Angle	Hitch Kit w/ 540 RPM Shaft c/w Non CV Drive Shaft	2,971.00	250	





This list supersedes all previous lists.

# USA

#### **MACHINE PRICES AND SPECIFICATIONS**

Effective January 1, 2022



### **FX-318 Pan Unit ROTARY CUTTER**

	ALC: N	-		-
1				

	~ ~ Selection 4 ~ Choo	se Chain Guard ~~
C318-500	Chain Guards Single Front and Rear	1,522.0
C318-550	Chain Guards Double Front and Rear	2,189.
C318-560	Front Half Belting (Must be used with a chain	option) 448.
C318-570	Rear Half Belting (Must be used with a chain	option) 479.
C318-580	Front Full Belting	510.
C318-590	Rear Full Belting	524.
	~ ~ Selection 5 ~ Ch	oose a Pan Kit ~ ~
C318-450	Pan Kit (required)	2,524.

600	
I	~ ~ Selection 6 ~ Choose a Blade Configuration ~ ~

C318-460	Updraft Blades, CW Center	512.00
C318-470	Shredder Blades, CW Center (optional)	853.00

1		A CONTRACTOR OF THE PARTY OF TH
C318-810	Wing Wheel Standard, 1 or 2 Tires Required	1,129.00
C318-800	Dual Wheel Standard on the Center Required	1,356.00

~ ~ Selection 7 ~ Choose Both Wheel Standard Kits ~ ~

	~ ~ Selection 8 ~	Choose an Axle Kit	~ ~
--	-------------------	--------------------	-----

C180-484	Axle Kit for 4 Tires	709.00	66
C180-486	Axle Kit for 6 Tires	1,064.00	99
C180-488	Axle Kit for 8 Tires	1,413.00	132

## ~ ~ Selection 9 ~ Choose a Tire Option ~ ~

# Please state the quantity of tires that you would like to order as the numbers listed below are single tires and not tire kits.

210-003WG	Solid Laminated Tires, 6 x 9 x 20	269.00	70
210-175WG	Forklift Tire 6.5 x 10 - 12 ply on 2 pce 5 bolt rim	393.00	40
210-175FWG	Foam Filled Forklift Tire 6.5 x 10 - 12 ply on 2 pce 5 bolt rim	693.00	
210-540WG	Tire 24x8-14 20 Ply Severe Duty	444.00	70
210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	718.00	
210-192WG	Solid Laminated Tire, 6 x 9 x 26	417.00	



This list supersedes all previous lists.



USA

MACHINE PRICES AND SPECIFICATIONS



### FX-318 Pan Unit ROTARY CUTTER

Effective January 1, 2022

~ ~ Selection 10 ~ Choose a Destination Code ~ ~

C318-NA

North American & Australian Decal Kit

56.00

~ ~ Selection 11 ~ Choose Extra Options ~ ~

C185-310

Independent Wing Lift

194.00

**Assembly Charge** 

Net

300.00

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

#### **IMPORTANT:**

- 1) Safety Chain Kit must be used at all times when moving equipment on any type of road.
- 2) OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown Object Shield Message in the Rotary Cutter Spec section in sales price book.





This list supersedes all previous lists.

## **USA** MACHINE PRICES AND SPECIFICATIONS

Effective January 1, 2022



## **FX-212 ROTARY CUTTER**



1,356.00

#### **CUTTER FEATURES**

- 540/1000 RPM 80° CV Drive
- 540 Equal angle non cv drive
- 7 ga Single Domed Deck and Stump Jumpers
- Rubber 3 Puck Grommet Suspension
- 90 HP Recommended Tractor

C318-800

- Cutting Width 144-1/2" (3.65m)

- Replaceable Skid Shoes
- Height Control Cylinder & Hoses
- Wing Lift Cylinders & Hoses
- 1.75" to 16.75" (44.5mm to 425mm) Cutting Height
- Over Center Folding Wings
- Transport Width 87"(2.4m)

~~9	Selection 1 ~ Choose a Basic Unit, Drive	Package ~ ~	
		Price USA	WT(lbs)
C319-100	FX-212, Basic Unit	20,806.00	
S000-085	Safety Light Kit (Required)	585.00	
DRIVE PA	ACKAGE (choose one)		
C319-735	CW Rotation on Center, 540 RPM G8 Shaft	4,100.00	in base
C319-720	CW Rotation on Center, 1000 RPM G8 Shaft	4,100.00	in base
	~ ~ Selection 2 ~ Choose a Hitch Optio	n ~ ~	1
C185-180 Choose	Trailing Hitch, CV Style a CV Shaft:	953.00	-3
a) 340-870	DWG CV Shaft, 540 RPM	1,453.00	
b) 340-648	CV Shaft, 1000 RPM	1,188.00	
C185-196	Equal Angle Hitch Kit w/ 540 RPM Shaft	2,971.00	
	~ ~ Selection 3 ~ Choose a Clevis ~	~	
C000-506WG	Open Clevis (Minimum Requirments)	428.00	,
C000-500WG	Precision hitch	741.00	
C000-510WG	Pro Level Hitch	578.00	
C000-513WG	Solid Tongue	466.00	
	~ ~ Selection 4 ~ Choose Axle Kits ^	~~	1
C319-810	Single Axle Kit for Right Wing (Required) (accomodates 1 or 2 tires)	440.00	3

**Duals Wheel Standard on Center (Required)** 



This list supersedes all previous lists.



### **USA** MACHINE PRICES AND SPECIFICATIONS

Effective January 1, 2022



### **FX-212 ROTARY CUTTER**

~	~	Selection	5 ^	Choose	a Sa	fety	Guard	~ ~
---	---	-----------	-----	--------	------	------	-------	-----

		Price USA	WT(lbs)
C319-500	Chain Guards Single Front & Rear	916.00	
C319-550	Chain Guards Double Front & Rear	1,240.00	
C319-560	Front Half Belting	291.00	
C319-570	Rear Half Belting	312.00	

#### ~ ~ Selection 6 ~ Choose The Pan Kit ~ ~

C319-450 Pan Kit (required) 1,549.00

#### ~ ~ Selection 7 ~ Choose a Blade Configuration ~ ~

C319-460 Updraft Blades, CW Center 324.00

### ~ ~ Selection 8 ~ Choose an Axle Kit ~ ~

C190-483	Axle Kit for 3 Tires	476.00
C190-485	Axle Kit for 5 Tires	790.00
C180-486	Axle Kit for 6 Tires	1,064.00

### ~ ~ Selection 9 ~ Choose a Tire Option ~ ~

## Please state the quantity of tires that you would like to order as the numbers listed below are single tires and not tire kits.

210-003WG	Solid Laminated Tires, 6 x 9 x 20	269.00
210-175WG	Tire Assy, Forklift, 6.5 x 10 - 12 ply on 2 pce 5 bolt rim	393.00
210-175FWG	Foam Filled Forklift Tire 6.5 x 10 - 12 ply on 2 pce 5 bolt rim	693.00
210-540WG	Tire 24x8-14 20 Ply Severe Duty	444.00
210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	718.00
210-192WG	Solid Laminated Tire, 6 x 9 x 26	417.00

### ~ ~ Selection 10 ~ Choose a Destination Code ~ ~

C319-NA North American & Australian Decal Kit 56.00
Assembly Charge Net 200.00

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

#### **IMPORTANT:**

2) OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown Object Shield Message in the Rotary Cutter Spec section in sales price book.



This list supersedes all previous lists.



### USA

#### MACHINE PRICES AND SPECIFICATIONS

Effective January 1, 2022



### FX-315 ROTARY CUTTER

#### **STANDARD & OPTIONAL CUTTER FEATURES**

- 7GA deck
- Transport width of 99"
- 4 gearbox drive layout
- Optional belting front or rear
- Hyd Phasing lift system
- 517 Hubs and axles

- Residue distribution tailboard
- Variable position shrouding
- Fixed knife technology
- Category 5 & 6 drivelines
- Rubber suspension standard
- Speed levelling system
- Replaceable deck protection rings
- Single domed, sweep clean deck
- Two piece replaceable skid shoes
- Pentagon blade bolt design
- Optional dbl safety chains front or rear
- Full floating front hitch

### ~ ~ Selection 1 ~ Choose a Basic Unit, Drive Package & Back Beam

				Price USA	Wt/lbs
1)	C316-100	FX-315 Rotary Cutter		23,612.00	3,630
2)	S000-095	Safety Light Kit (Requ	uired)	598.00	
•	a)	C306-705 Drive Pa	ackage, CW Center, 540 RPM	6,370.00	
	b)	C306-715 Drive Pa	ackage, CW Center, 1000 RPM	6,370.00	
	Must Choo	se the Center Back Bear	n		
1)	C316-115	Standard Back Beam		2,197.00	222
		~ ~ Selection	2 ~ Choose a Hitch Type and Accessories ~	~	
1)	C316-270	Trailing CV hitch Kit		1,099.00	139
	Cho	ose a Clevis:			
	a)	C000-506WG	Open Clevis	428.00	11
	b)	C000-510WG	Pro Level Clevis	578.00	15
	c)	C000-500WG	Precision hitch	741.00	29
	d)	C000-513WG	Solid Tongue	466.00	13
	e)	C000-515WG	Clevis with 2 3/16" Opening	526.00	13
	Cho	ose a Tractor Shaft:			
	a)	340-870WG	CV Shaft, 540 RPM	1,453.00	75
	b)	340-648WG	CV Shaft, 1000 RPM	1,188.00	62
2)	C316-185	Equal Angle Non-CV h	itch Kit w/ 540 RPM Shaft	3,149.00	260
3)	C316-196	Parallel Ring hitch		1,666.00	224
	a)	230-015WG	Pintle Ring, Forged, PT-48 (Installed on Parallel Hitch)	159.00	
		ose Tractor Shaft			
	b)	340-648WG	CV Shaft, 1000 RPM	1,188.00	
4)	C316-195	German high hitch		2,585.00	
	a) <i>Cho</i>	230-015WG ose Tractor Shaft	Pintle Ring, Forged, PT-48 (Installed on German High Hitch)	159.00	
	b)	340-648WG	CV Shaft, 1000 RPM	1,188.00	62



This list supersedes all previous lists.



USA

**MACHINE PRICES AND SPECIFICATIONS** 

Effective January 1, 2022



## **FX-315 ROTARY CUTTER**

~ ~ Selection 3 ~ Choose a Skid ~ ~

1) C316-215 Regular Skids

Price USA Wt/lbs 367.00 15

~	~	Selection 4	. ~	Choose	a Safety	<b>Guard</b>	Kit	~	~

1)	C316-500	Chain Guards Double Front	NOTE: Any combination of chains &	1,376.00	280
2)	C316-510	Chain Guards Double Rear	belting can be used	1,171.00	202
3)	C316-550	Full Front Belting		474.00	112
4)	C316-560	Full Rear Belting	NOTE: When ordering Residue Distribution Tailboard NO rear guards are needed	344.00	88
5)	C316-320	Residue Distribution Tailboard  Recommended with C316-460	_	3,195.00	323

**IMPORTANT:** Safety Tow Chain Kit must be used at all times when moving equipment on any type of road.

**IMPORTANT:** OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown ObjectShield Information Message in the Rotary Cutter Spec Section in the sales price book.



This list supersedes all previous lists.

Effective January 1, 2022

USA

#### **MACHINE PRICES AND SPECIFICATIONS**



## **FX-315 ROTARY CUTTER**



_~	~ Selection :	5 ~ Choose Pan Kit or Fixed Knife Blade Config	uration ~	~
			Price USA	Wt/lbs
1)	C316-440 Pan Kit		2,198.00	123
	Choose a blade configur			
	a) C316-451	Updraft Blades, CW Center	506.00	35
	b) C316-453	Shredder Blades, CW Center	861.00	64
	Optional			
	a) C316-455	Bolt-On Deck Ring Option for Pan Kit	1,074.00	113
2)	C316-460 Fixed Knife	Bars, Blades (Updraft), Mounts, CW Rotation on Center	3,808.00	213
3)	C316-220 Variable Pos	sition Shrouding (recommended with C316-460)	1,342.00	64
		N. Calastian C. N. Chanca An Ania Kit. M. M.	1	
	and pulse of a special control of the special	~ Selection 6 ~ Choose An Axle Kit ~ ~		
1)	C316-484	Axle Kit for 4 Tires	592.00	36
2)	C316-486	Axle Kit for 6 Tires	1,155.00	50
3)	C316-488	Axle Kit for 8 Tires	1,682.00	66
	~	~ Selection 7 ~ Choose A Tire Option ~ ~		
		The state of the s		
1)	210-003WG	Solid Laminated Tire, 6 x 9 x 20	269.00	28
2)	210-540WG	Tire 24x8-14 20 Ply Severe Duty	444.00	32
3)	210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	718.00	
4)	210-175WG	Tire Assy, Forklift, 6.50x10-12 Ply Rated on 2pce Bolt Rim	393.00	18
5)	210-175FWG	Foam Filled Forklift Tire 6.5 x 10 - 12 ply on 2 pce 5 bolt rim	693.00	
6)	210-192WG	Solid Laminated Tire, 6 x 9 x 26	417.00	



This list supersedes all previous lists.



USA

MACHINE PRICES AND SPECIFICATIONS



### **FX-315 ROTARY CUTTER**

Effective January 1, 2022

Selection 8 ~ Choose a Destination Code

### Please select the destination of the cutter for proper <u>Decals</u>, <u>Manuals</u> and <u>CE Shielding Upgrade</u>.

			Price USA	Wt/lbs		
1)	C316-NA	North American English Destination Kit 585.00				
2)	C316-FR	France Destination Kit 658.00				
3)	C316-DE	German Destination Kit 648.00				
		~ ~ Selection 9 ~ Extra Options ~ ~				
1)	C316-200	<b>Chock Blocks Selection 9 ~ Extra Options ~ ~</b>	334.00	50		

Assembly Charge

Net

300.00

**OPTIONAL PDI INCLUDES:** greasing of all pivot points, gearbox oil checked, charge hydraulic cylinders and install pioneer ends. Tires will be installed where necessary. It is the dealers responsibility to remove shipping brackets & banding as well as to adjust mower height as specified in the operators manual. Please go to the Schulte website/dealer access for further information.



This list supersedes all previous lists.



#### USA

#### **MACHINE PRICES AND SPECIFICATIONS**

Effective January 1, 2022



### XH1500 Series 5 Rotary Cutter

#### **CUTTER FEATURES**

- 7GA deck
- Replaceable skid shoes
- Double safety chains front & rear
- Hydraulic phasing lift system
- Hydraulic wing lift system
- 517 Hubs and axles

- Single domed, sweep clean deck
- Rubber suspension standard
- Four gearbox drive layout 240hp down, 275hp splitter
- Full floating front hitch
- Deck protection rings
- S000-010 safety chain kit 1/4" grade 70 with 10,000 lbs capacity
- 1/4" Round skid pans (Stump Jumpers)
- Pentagon blade bolt design
- Operator's manual in holder

#### ~ ~ Selection 1 ~ Choose a Basic Unit ~ ~

			Price USA	Wt/kgs
C350-100	Basic Unit X	H Series 5	20,114.00	
C350-200	15' Option (	Required)	16,371.00	
S000-160	Safety Light	Kit (Required)	592.00	
Cho	ose a Drive P	ackage:		
a)	C350-705	CW Rotation Center 540 RPM (Std. Rotation)	6,345.00	
b)	C350-715	CW Rotation Center 1000 RPM (Std. Rotation)	6,345.00	
c)	C350-700	OR CCW Rotation on Center 540 RPM (Non Std Rotation)	6,345.00	
d)	C350-710	OR CCW Rotation on Center 1000 RPM (Non Std. Rotation)	6,345.00	
	C350-200 S000-160 Cho a) b)	C350-200 15' Option ( S000-160 Safety Light Choose a Drive P a) C350-705 b) C350-715 c) C350-700	C350-200 15' Option (Required) S000-160 Safety Light Kit (Required) Choose a Drive Package: a) C350-705 CW Rotation Center 540 RPM (Std. Rotation) b) C350-715 CW Rotation Center 1000 RPM (Std. Rotation) c) C350-700 OR CCW Rotation on Center 540 RPM (Non Std Rotation)	C350-100       Basic Unit XH Series 5       20,114.00         C350-200       15' Option (Required)       16,371.00         S000-160       Safety Light Kit (Required)       592.00         Choose a Drive Package:

### ~ ~ Selection 2 ~ Choose a Hitch Type and Accessories ~ ~

1)	C350-180	Trailing Hitch CV Style		971.00
Τ,		,		371.00
	Cho	ose a Clevis:		
	a)	C000-506WG	Open Clevis (Minimum Requirement with a Flex Arm)	428.00
	b)	C000-500WG	Precision Hitch (Can be used with a Flex Arm)	741.00
	c)	C000-513WG	Solid tongue (Can be used with a Flex Arm)	466.00
	d)	C000-515WG	Clevis 2 3/16 " opening (Can be used with a Flex Arm)	526.00
	e)	C000-510WG	Pro Level Hitch (Can <u>NOT</u> be used with a Flex Arm)	578.00
	Cho	ose a Tractor Shaft:		
	a)	340-870WG	CV Shaft, 540 rpm	1,453.00
	b)	340-648WG	CV Shaft, 1000 rpm	1,188.00
	c)	340-658WG	CV Shaft 1000 RPM 1 3/4" shaft	1.630.00

### ~ ~ Selection 3 ~ Choose Hydraulic Option ~ ~

1)	C350-805	Independent Double Acting Hose Kit OR	385.00
2)	C350-810	Double Acting Hose Kit - "Teed" - for tractors w/ 2 valve banks	360.00



This list supersedes all previous lists.



## USA

#### **MACHINE PRICES AND SPECIFICATIONS**

Effective January 1, 2022



### XH1500 Series 5 Rotary Cutter

### ~ ~ Selection 4 ~ Choose a Blade Configuration ~ ~

			Price USA	wt/kgs
1)	C350-450	2 Blade Pan Kit - cw Schulte Super Suction Updraft 4" Blades	354.00	
2)	C350-451	2 Blade Pan Kit - ccw Schulte Super Suction Updraft 4" Blades	354.00	
3)	C350-455	2 Blade Pan Kit - cw Schulte Super Suction Updraft 5" Blades	439.00	
4)	C350-456	2 Blade Pan Kit - ccw Schulte Super Suction Updraft 5" Blades	439.00	

#### ~ ~ Selection 5 ~ Choose a Center Axle Kit ~ ~

1)	C350-820	Walking (Axles Included)	1,758.00
~ 1	C250 025	Non-Maildon / The Wh. Auton Individed)	044.00

#### 2) C350-825 Non Walking (4 Tire Kit, Axles Included) 811.00

### ~ ~ Selection 6 ~ Choose a Wing Axle Kit ~ ~

1)	C350-820	Walking (Axles included)	1,758.00
2)	C350-830	Non Walking (2 Tire Kit, Axles Included)	525.00
21	C350_935	Non Walking Id Tire Kit Ayles Included)	911.00

### ~ ~ Selection 7 ~ Choose a Tire Option ~ ~

Please state the quantity of tires that you would like to order as the numbers listed below are just single tires and not a tire kit.

	listed pelow are just	single tires and not a tire kit.		
			Price USA PRICE PER TIRE	Wt/lbs
			PRIOR PER TINE	
1)	210-186WG	27 X 10.5-15 Skid Steer Tire, LEFT	425.00	
2)	210-187WG	27 X 10.5-15 Skid Steer Tire, RIGHT	425.00	
	NOTE: If choosing skid	steer tires, be sure to choose correct amount of left & right tires		
3)	210-182WG	Aircraft Tire (29 x 9-15/16 Ply)	453.00	
4)	210-182FWG	Foam Filled Aircraft Tire (29 x 9-15/16 Ply)	675.00	
5)	210-192WG	Solid Laminated Tire, 6 x 9 x 26	417.00	

### ~ ~ Selection 8 ~ Choose a Destination Package ~ ~

Please select the destination of the cutter for proper Decals, Manuals, and Shielding

1) C350-NA North American/ Australia Destination Kits



This list supersedes all previous lists.



#### USA

#### **MACHINE PRICES AND SPECIFICATIONS**

Effective January 1, 2022



## XH1500 Series 5 Rotary Cutter

All distances		The same	1	100	
-					

### ~ ~ Selection 9 ~ Extra Options ~ ~

		Assembly Charge	Net	300.00	
4)	C306-305	Flex Arm Mount		201.00	
3)	C350-885	Left Hand Gauge Wheel Kit		827.00	
2)	C350-880	Right Hand Gauge Wheel Kit		827.00	
1)	C350-540	Rear Half Belting Kit		494.00	
				Price USA	Wt/kgs

<u>OPTIONAL PDI INCLUDES</u>: greasing of all pivot points, gearbox oil checked, charge hydraulic cylinders and install pioneer ends. Tires will be installed where necessary. It is the dealers responsibility to remove shipping brackets & banding as well as to adjust mower height as specified in the operators manual. Please go to the Schulte website/dealer access for further information.



This list supersedes all previous lists.



#### USA

#### **MACHINE PRICES AND SPECIFICATIONS**





### XH1000 Series 5 Rotary Cutter



#### **CUTTER FEATURES**

- 7GA deck
- Replaceable skid shoes
- Double safety chains front & rear
- Hydraulic phasing lift system
- Hydraulic wing lift system
- 517 Hubs and axles
- Single domed, sweep clean deck
- Rubber suspension standard
- Four gearbox drive layout 240hp down, 275hp splitter
- Full floating front hitch
- Deck protection rings
- S000-010 safety chain kit 1/4" grade 70 with 10,000 lbs capacity
- 1/4" Round skid pans (Stump Jumpers)
- Pentagon blade bolt design
- Operator's manual in holder

#### ~ ~ Selection 1 ~ Choose a Basic Unit and Drive Package~ ~

				Price USA	Wt/kgs
1)	C350-100	Basic Unit X	H Series 5	20,114.00	
2)	C350-250	10' Option	(Required)	15,223.00	
3)	S000-165	Safety Light	Kit (Required)	565.00	
	Cho	ose a Drive P	ackage:		
	a)	C350-745	CW Rotation on Center, 540 RPM, (Std. Rotation)	4,500.00	
	b)	C350-755	CW Rotation on Center, 1000 RPM (Std. Rotation)	4,500.00	

### ~ ~ Selection 2 ~ Choose a Hitch Type and Accessories ~ ~

1)	C350-180	Trailing Hitch CV Style		971.00	63
	Cho	ose a Clevis:			
	a)	C000-506WG	Open Clevis (Minimum Requirement with a Flex Arm)	428.00	5
	b)	C000-500WG	Precision Hitch (Can be used with a Flex Arm)	741.00	13
	c)	C000-513WG	Solid tongue (Can be used with a Flex Arm)	466.00	6
	d)	C000-515WG	Clevis 2 3/16 " opening (Can be used with a Flex Arm)	526.00	6
	e)	C000-510WG	Pro Level Hitch (Can NOT be used with a Flex Arm)	578.00	
	Cho	oose a Tractor Shaft:			
	a)	340-870WG	CV Shaft, 540 rpm	1,453.00	35
	b)	340-648WG	CV Shaft, 1000 rpm	1,188.00	27
	c)	340-658WG	CV Shaft 1000 RPM 1 3/4" shaft		

### ~ ~ Selection 3 ~ Choose Hydraulic Option ~ ~

C350-815 Independent Double Acting Hose Kit Required



This list supersedes all previous lists.



#### USA

#### **MACHINE PRICES AND SPECIFICATIONS**

Effective January 1, 2022



## XH1000 Series 5 Rotary Cutter

### ~ ~ Selection 4 ~ Choose a Blade Configuration ~ ~

1) C350-470 2 Blade Pan kit - CW Schulte Super Suction Updraft 4" Blades 237.00

2) C350-475 2 Blade Pan kit - CW Schulte Super Suction Updraft 5" Blades 295.00

### ~ ~ Selection 5 ~ Choose a Center Axle Kit ~ ~

 1) C350-820
 Walking Axle (Axles Included)
 1,758.00

 2) C350-825
 Non Walking (4 Tire Kit, Axles Included)
 811.00

### ~ ~ Selection 6 ~ Choose a Wing Axle Kit ~ ~

 1)
 C350-835
 Walking Axle (Axle Included)
 880.00

 2)
 C350-840
 Non Walking (1 Tire Kit, Axle Included)
 263.00

 3)
 C350-845
 Non Walking (2 Tire Kit, Axles Included)
 407.00

### ~ ~ Selection 7 ~ Choose a Tire Option ~ ~

Please state the quantity of tires that you would like to order as the numbers listed below are just single tires and not a tire kit.

Price USA Wt/lbs **PRICE PER TIRE** 1) 210-186WG 27 X 10.5-15 Skid Steer Tire, LEFT 425.00 2) 210-187WG 27 X 10.5-15 Skid Steer Tire, RIGHT 425.00 NOTE: If choosing skid steer tires, be sure to choose correct amount of left & right tires 3) 210-182WG Aircraft Tire (29 x 9-15/16 Ply) 453.00 210-182FWG Foam Filled Aircraft Tire (29 x 9-15/16 Ply) 675.00 210-192WG Solid Laminated Tire, 6 x 9 x 26 417.00

## ~ ~ Selection 8 ~ Choose a Destination Package ~ ~

Please select the destination of the cutter for proper Decals, Manuals, and Shielding

1) C350-NA10 North American/ Australia Destination Kits



This list supersedes all previous lists.



#### USA

#### **MACHINE PRICES AND SPECIFICATIONS**

Effective January 1, 2022



### **XH1000 Series 5 Rotary Cutter**

Checkive danidary 1, 2022

### ~ ~ Selection 9 ~ Extra Options ~ ~

Price USA Wt/kgs

1) C350-550 XH1000 S5 Rear Half Belting Kit

364.00

827.00

2) C350-880 Right Hand Gauge Wheel Kit

027.00

3) C306-305 Flex Arm Mount

201.00

IMPORTANT: Safety Tow Chain Kit must be used at all times when moving equipment on any type of road.

**Assembly Charge** 

Net

200.00

<u>OPTIONAL PDI INCLUDES</u>: greasing of all pivot points, gearbox oil checked, charge hydraulic cylinders and install pioneer ends. Tires will be installed where necessary. It is the dealers responsibility to remove shipping brackets & banding as well as to adjust mower height as specified in the operators manual. Please go to the Schulte website/dealer access for further information.



This list supersedes all previous lists.



#### **MACHINE PRICES AND SPECIFICATIONS**





## **FX-1800 Pan ROTARY CUTTER**

Effective January 1, 2022

#### **CUTTER FEATURES**

- 540/1000 RPM Drive
- 7 ga. Spun Formed Stump Jumpers
- -Replaceable Skid Shoes
- 7 ga Single Domed Deck
- Deck Protection Rings
- Over Center Folding Wings

- 80 Degree CV Drive

- Height Control Cylinder & Hoses
- -Wing Lift Cylinders & Hoses
- S000-010 Safety Chain (1/4" gr.70 10000lbs cap.)
- Operator's and Parts Manual Holder
- Cutting Width 180" (4.57m)
- Transport Width (max with duals on wings) 102"(2.59m

more specs on brochure

<u>'</u>	Selection 1 ~ Choose a Basic Unit, Drive Package ~ ~				
		Price USA	WT(lbs)		
C185-100	Schulte FX-1800, Basic Unit	18,160.00	5,113		
S000-085	Safety Light Kit (Required)	585.00			
Choose a Driv	_				
a)	C306-705 Drive Package, CW Center, 540 RPM	6,370.00	in base		
b)	C306-715 Drive Package, CW Center, 1000 RPM	6,370.00	in base		
	~ ~ Selection 2 ~ Choose a Hitch Option ~ ~				
C185-180	Trailing Hitch, CV Style	953.00	13		
Choose a C	V Shaft:				
a)	<b>340-870WG</b> CV Shaft, 540 RPM	1,453.00	74		
b)	<b>340-648WG</b> CV Shaft, 1000 RPM	1,188.00	60		
c)	<b>340-658WG</b> CV Shaft 1000 RPM 1 3/4" shaft	1,630.00	60		
C185-196	Equal Angle Hitch Kit w/ 540 RPM Shaft	2,971.00	250		
	~ ~ Selection 3 ~ Choose a Clevis ~ ~				
C000-506WG	Open Clevis (Minimum Requirement with a Flex Arm)	428.00	11		
C000-500WG	Precision Hitch (Can be used with a Flex Arm)	741.00	28		
C000-513WG	Solid tongue (Can be used with a Flex Arm)	466.00	13		
C000-510WG	Pro Level Hitch (Can <u>NOT</u> be used with a Flex Arm)	578.00			
	~ ~ Selection 4 ~ Choose a Center Axle Mount Style ^	~			
C185-870	Standard Axle Mounts	571.00			
C185-875	Walking Axle Mounts	1,782.00			
	~ ~ Selection 5 ~ Choose a Wing Axle Mount Style ~	~			
C185-870	Standard Axle Mounts	571.00			
C185-875	Walking Axle Mounts	1,782.00			





This list supersedes all previous lists.

USA

#### **MACHINE PRICES AND SPECIFICATIONS**

Effective January 1, 2022



#### FX-1800 Pan ROTARY CUTTER

	~ ~ Selection 6 ~ Choose a Safety Guard ~ ~		
C180-520	Chain Guards Single Front and Rear	1,135.00	206
C180-500	Chain Guards Double Front and Rear	1,555.00	308
	~ ~ Selection 7 ~ Choose a Pan Kit ~ ~		
C316-450	Pan Kit (required)	2,019.00	270
	~ ~ Selection 8 ~ Choose a Blade Configuration ~ ~		
C316-451	CW Schulte Super Suction Updraft 4" Blades	506.00	77
C316-459	CW Schulte Super Suction Updraft 5" Blades	679.00	80
C316-453	Shredder Blades, CW Center	861.00	143
	~ ~ Selection 9 ~ Choose an Axle Kit ~ ~		
C180-484	Axle Kit for 4 Tires	709.00	66
C180-486	Axle Kit for 6 Tires	1,064.00	99
C180-488	Axle Kit for 8 Tires	1,413.00	132
	~ ~ Selection 10 ~ Choose a Tire Option ~ ~		

Please state the quantity of tires that you would like to order as the numbers listed below are single tires and not tire kits.

210-003WG	Solid Laminated Tires, 6 x 9 x 20	269.00	70
210-175WG	Forklift Tire 6.5 x 10 - 12 ply on 2 pce 5 bolt rim	393.00	40
210-175FWG	Foam Filled Forklift Tire 6.5 x 10 - 12 ply on 2 pce 5 bolt rim	693.00	
210-540WG	Tire 24x8-14 20 Ply Severe Duty	444.00	70
210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	718.00	
210-192WG	Solid Laminated Tire, 6 x 9 x 26	417.00	

## ~ ~ Selection 11 ~ Choose a Destination Code ~ ~

C185-NA North American & Australian Decal Kit



This list supersedes all previous lists.





**MACHINE PRICES AND SPECIFICATIONS** 





## FX-1800 Pan ROTARY CUTTER

Effective January 1, 2022

	~ ~ Selection 12 ~ Choose Extra Options ~ ~			
C185-304	Mount Assembly for Flex Arm Strut, (Factory Installed)		802.00	2
C185-305	Mount Assembly for Flex Arm Strut, (parts only)		332.00	2
C185-325	Tension Link Leveling Rod , Factory Installed		285.00	4
C185-330	Tension Link Leveling Rod , Weld on Parts only		356.00	4
C185-310	Hose Kit, independent wing-lift		194.00	10
	Assembly Charge on Pan Units	let	300.00	

#### PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

#### **IMPORTANT:**

- 1) Safety Chain Kit must be used at all times when moving equipment on any type of road.
- 2) OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown Object Shield Message in the Rotary Cutter Spec section in sales price book.





This list supersedes all previous lists.

## **USA** MACHINE PRICES AND SPECIFICATIONS

Effective January 1, 2022



## **FX-1200 ROTARY CUTTER**



#### **CUTTER FEATURES**

- 540/1000 RPM Drive
- 7 ga. Spun Formed Stump Jumpers
- -Replaceable Skid Shoes
- 7 ga Single Domed Deck
- Deck Protection Rings
- Over Center Folding Wings

- 80 Degree CV Drive
- Height Control Cylinder & Hoses
- -Wing Lift Cylinders & Hoses
- S000-010 Safety Chain (1/4" gr.70 10000lbs cap.)
- Operator's and Parts Manual Holder
- Cutting Width 126" (3.20m)
- Transport Width (max with duals on wings)97.5"(2.47m)

more specs on brochure

~~Se	election 1 ~ Choose a Basic Unit, Drive Pack	age ~ ~	
		Price USA	WT(lbs)
C195-100	FX1200, Basic Unit	18,863.00	4,863
S000-085	Safety Light Kit (Required)	585.00	
DRIVE PAC	KAGE (choose one)		
C307-700	CW Rotation on Center, 540 RPM	4,671.00	in base
C307-710	CW Rotation on Center, 1000 RPM	4,671.00	in base
	~ ~ Selection 2 ~ Choose a Hitch Option ~ ^	,	
C185-180 Choose a 0	Trailing Hitch, CV Style CV Shaft:	953.00	204
a) 340-870W		1,453.00	75
b) 340-648W	G CV Shaft, 1000 RPM	1,188.00	220
C185-196	Equal Angle Hitch Kit w/ 540 RPM Shaft	2,971.00	250
	~ ~ Selection 3 ~ Choose a Clevis ~ ~		
C000-506WG	Open Clevis (Minimum Requirement with a Flex Arm)	428.00	11
C000-500WG	Precision Hitch (Can be used with a Flex Arm)	741.00	28
C000-513WG	Solid tongue (Can be used with a Flex Arm)	466.00	13
C000-510WG	Pro Level Hitch (Can <u>NOT</u> be used with a Flex Arm)	578.00	
	Selection 4 ~ Choose a Center Axle Mount St	vle~ ~	
C185-870	Standard Axle Mounts	571.00	
C185-875	Walking Axle Mounts	1,782.00	
~~	Selection 5 ~ Choose a Wing Axle Mount Sty	ıle~ ~	
C195-870	Standard Axle Mount	298.00	<del></del>
C195-875	Walking Axle Mount	882.00	



This list supersedes all previous lists.

**USA** MACHINE PRICES AND SPECIFICATIONS

Effective January 1, 2022



## **FX-1200 ROTARY CUTTER**

~ ~ Selection 6 ~	Chanse of	Safety	Guard	~ ~
JEIECHUII U	CHOUSE U	<i>i Juic</i> ly	Quuiu	

		Price USA	WI(lbs)
C190-520	Chain Guards Single Front & Rear	780.00	137
C190-500	Chain Guards Double Front & Rear	1,066.00	205
			-1

### ~ ~ Selection 7 ~ Choose The Pan Kit ~ ~

C317-450	Pan Kit (required)	1,334.00	190
Contract of the last of the la	The state of the s	7	

## ~ ~ Selection 8 ~ Choose a Blade Configuration ~ ~

C317-451	Updraft Blades, CW Center	316.00	70
C317-453	Shredder Blades, CW Center	500.00	115

the second section is a second second second	THE RESERVE THE PERSON NAMED IN COLUMN TWO IS NOT THE OWNER.		THE RESIDENCE OF THE PARTY OF T	the Person of th
	~ ~ Selection	9 ~	Choose an	Axle Kit ~ ~

C190-483	Axle Kit for 3 Tires	476.00	51
C190-485	Axle Kit for 5 Tires	790.00	84
C180-486	Axle Kit for 6 Tires	1,064.00	99

## ~ ~ Selection 10 ~ Choose a Tire Option ~ ~

## Please state the quantity of tires that you would like to order as the numbers listed below are single tires and not tire kits.

210-003WG	Solid Laminated Tires, 6 x 9 x 20	269.00	70
210-175WG	Tire Assy, Forklift, 6.5 x 10 - 12 ply on 2 pce 5 bolt rim	393.00	74
210-175FWG	Foam Filled Forklift Tire 6.5 x 10 - 12 ply on 2 pce 5 bolt rim	693.00	
210-540WG	Tire 24x8-14 20 Ply Severe Duty	444.00	70
210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	718.00	
210-192WG	Solid Laminated Tire, 6 x 9 x 26	417.00	

### ~ ~ Selection 11 ~ Choose a Destination Code ~ ~

C195-NA North American & Australian Decal Kit

52.00



This list supersedes all previous lists.



**USA** 

MACHINE PRICES AND SPECIFICATIONS





## FX-1200 ROTARY CUTTER

Effective January 1, 2022

	Selection 12 ~ Choose a Extra Options ~ ^		J
C185-304	Mount Assembly for Flex Arm Strut, (Factory Installed)	802.00	25
C185-305	Mount Assembly for Flex Arm Strut, (parts only)	332.00	25
C185-325	Tension Link Leveling Rod , Factory Installed	285.00	41
C185-330	Tension Link Leveling Rod , Weld on Parts only	356.00	41

**Assembly Charge** 

Net

200.00

#### PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

#### **IMPORTANT**:

2) OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown Object Shield Message in the Rotary Cutter Spec section in sales price book.



This list supersedes all previous lists.

## USA

#### **MACHINE PRICES AND SPECIFICATIONS**



#### **GX-150 ROTARY CUTTER**



#### **CUTTER FEATURES**

- -540/1000 RPM Drive
- High inertia blade carrier
- Replaceable Skid Shoes
- 10 ga Single Domed Deck
- Deck Protection Rings
- Over Center Folding Wings

- 80 Degree CV Drive
- Height Control Cylinder & Hoses
- -Wing Lift Cylinders & Hoses
- S000-010 Safety Chain (1/4" gr.70 10000lbs cap.)
- Operator's and Parts Manual Holder
- Cutting Width 180" (4.57m)

	~ ~ Select	<u>ion 1 ~ Choose a Basic Unit, Drive Package</u>	, ~ ~	
			Price USA	WT(kgs)
C170-100	GX-150 Base	! Unit	17,389.00	
S000-085	Safety Light	Kit (Required)	585.00	
Choose a Driv	e Package:			
a)	C170-705	Drive Package, CW Center, 540 RPM	4,426.00	
b)	C170-715	Drive Package, CW Center, 1000 RPM	4,426.00	
	~ .	Selection 2 ~ Choose a Hitch Option ~ ~		
C185-180	Trailing Hite	h, CV Style	953.00	
Choose a C				
a)	340-835W		892.00	
b)	340-675W	CV Shaft, 1000 RPM	744.00	] []
		~ ~ Selection 3 ~ Choose a Clevis ~ ~		
C000-510WG	Pro Level H	itch (Required)	578.00	2. ) S
	~ ^	Selection 4 ~ Choose a Safety Guard ~~		
C180-520	Chain Guar	ds Single Front and Rear	1,135.00	94
C180-500	Chain Guar	ds Double Front and Rear	1,555.00	)
		~ ~ Selection 5 ~ Choose a Pan Kit ~ ~		
C170-450	Pan Kit (re	quired)	1,766.00	123





#### USA

#### **MACHINE PRICES AND SPECIFICATIONS**

Effective January 1, 2022



#### **GX-150 ROTARY CUTTER**

	~ ~ Selection 6 ~ Choose a Blade Configuration ~ ~	
316-451	CW Schulte Super Suction Updraft 4" Blades Or	506.00
	~ ~ Selection 7 ~ Choose an Axle Kit ~ ~	
180-484	Axle Kit for 4 Tires (Two tires on center, one tire on each wing)	709.00
180-486	Axle Kit for 6 Tires (Duals on center, one tire on each wing)	1,064.00
180-488	Axle Kit for 8 Tires (Duals on center, duals on wings)	1,413.00
	~ ~ Selection 8 ~ Choose a Tire Option ~ ~	

Please state the quantity of tires that you would like to order as the number listed below is single tires and not tire kits.

210-175WG 210-195WG 210-003WG	Forklift Tire 6.5 $\times$ 10, 12 ply rated on 2 pce 5 bolt rim Solid Laminated Tire, 6 $\times$ 9 $\times$ 26 Solid Laminated Tires, 6 $\times$ 9 $\times$ 20	393.00 293.00 269.00	32
	~ ~ Selection 9 ~ Choose a Destination Code	~~	
C170-NA	North American & Australian Decal Kit	54.00	
	~ ~ Selection 10 ~ Choose Extra Options ~	~	
C185-325	Tension Link Leveling Rod , Factory Installed	285.00	19
	Assembly Charge on Pan Units	Net <b>300.00</b>	

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

#### **IMPORTANT:**

- 1) Safety Chain Kit must be used at all times when moving equipment on any type of road.
- 2) OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown Object Shield Message in the Rotary Cutter Spec section in sales price book.



This list supersedes all previous lists.



#### USA

MACHINE PRICES AND SPECIFICATIONS





## FX-209 Rotary Cutter

Effective January 1, 2022

#### **CUTTER FEATURES - ALL HITCH TYPES**

- Push or pull capability
- 9ft / 3m overall width

C209-300

- Cutting Height: 2" 13" (5.1 cm 33 cm)
- Cutting Width: 109.25" (2.78 m)
- Cutting Capacity: 3" (7.6 cm)
- Minimum Tractor HP 50 HP ( 37.3 kW)

- Gearbox Rating 210 hp
- Two rotor base unit common to all configuration
- Pans with Schulte Super Suction Blades
- Double Chain Front & Rear
- -7 Ga Deck
- 540 and 1000 RPM drive options
- Cat. II & III 3 Point / Semi Mount Swing (13" left or right swing), Trailing Pull

or

#### ~ ~ Selection 1 ~ Choose a FX-209 Base Unit ~ ^

Price USA

Wt/lbs

C209-100 FX-209 Base Unit 9,937.00

2.325.00

### ~ ~ Selection 2 ~ Choose a FX-209 Non Trailing Configuration

#### **Choose One Mount** 3PT Mount Option

0200 000		/
C209-360	Semi Mount Swing or	3,497.00
C209-370	Semi Mount	1,395.00
	Choose One Drive Package	
C209-710	540 RPM Drive Package NON-TRAILING or	1,915.00
C209-715	1000 RPM Drive Package NON-TRAILING	1,915.00
C209-720	Front Frame Pushing 540 RPM Drive (only to be used with	2,873.00
FM-115	or FM350 Front mount 3pt frame Not needed with Tractor front 3pt sy	
	Choose One Wheel Assembly	
C209-400	FX-209 Wheel Assembly Non-Trailing Standard or	2,402.00
C209-450	FX-209 Wheel Assembly Non-Trailing Hydraulic	3,420.00

## ~ ~ Selection 3 ~ Choose a FX-209 Trailing Hitch Configuration ~ ~

C209-340	FX-209 Trailing Hitch		4,681.00
CS01-106WG	Open Clevis (Minimum Requirement	nt) or	204.00
C000-360WG	Adjustable Clevis	or	357.00
C000-300WG	Precision Hitch	or	565.00
C502-113WG	Solid Tongue		245.00
Choose Or	ne Drive Package		
C209-700	540 RPM Drive Package Trailing	or	3,493.00
C209-705	1000 RPM Drive Package Trailing		3,493.00





## **USA**



## FX-209 Rotary Cutter



Effective January 1, 2022

~ ~	Selection 4	~	Choose	<b>Options</b>	~ ~
-----	-------------	---	--------	----------------	-----

C209-250 C209-520 Blade Pan Option (Must Pick)

Half Length Belting Option (Front and Back)

**Price USA** 

Wt/lbs

1,571.00 267.00

### Selection 5 ~ Choose Tire Options ~~

#### (CHOOSE 2 TIRES PER UNIT)

210-003WG	Solid Laminated Tires, 6 x 9 x 20	269.00
210-540WG	Tire 24x8-14 20 Ply Severe Duty	444.00
210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	718.00
210-175WG	Forklift New, 6.5 x 10 - 12 ply rated on 2 pcs 5 bolt rim	393.00
210-175FWG	Foam Filled Forklift Tire 6.5 x 10 - 12 ply on 2 pce 5 bolt rim	693.00

**Assembly** 

Net



This list supersedes all previous lists.



#### USA

#### **MACHINE PRICES AND SPECIFICATIONS**





## FX-107 Rotary Cutter

Effective January 1, 2022

#### **CUTTER FEATURES - ALL HITCH TYPES**

- Rigid single domed 7 gauge deck construction
- Overall width: 95.5" ( 2.43 m)
- Cutting Height: 3" 12 7/8" (7.6 cm 33 cm)
- Cutting Width: 84" (2.13 m)
- Cutting Capacity: 3" (7.6 cm)
- Minimum Tractor HP 50 HP ( 37.3 kW)
- Cat. II & III 3 Point / Trailing Pull

- Pull type and 3 point hitch options
- Base unit common to all configurations
- 540 RPM drive
- Double Chain Front & Rear
- 7 Ga Deck
- Pull type unit has the ability to accept open clevis, solid tongue & adjustable clevis

#### ~ ~ Selection 1 ~ Choose a Base Unit ~ ~

Wt/lbs Price USA

C107-100

FX-107 Base Unit

#### ~ ~ Selection 2 ~ Choose a 3 Point Option Configuration

C107-300

3PT Mount Option (if this choosen skip Trailing Hitch Option)

3,927.00

6,631.00

### ~ ~ Selection 3 ~ Choose a Trailing Hitch Configuration ~ ~

C107-195	Trailing Hitch or		5,884.00
CS01-106WG	Open Clevis (Minimum Requirement	t) or	204.00
C000-360WG	Adjustable Clevis	or	357.00
C000-300WG	Precision Hitch	or	565.00
C502-113WG	Solid Tongue		245.00

### Selection 4 ~ Blade Pan Option ~ ~

C107-250

Blade Pan Option (Must Pick)

1,046.00

#### Selection 5 ~ Choose Tire Options ~~

#### (CHOOSE 2 TIRES PER UNIT)

210-003WG	Solid Laminated Tires, 6 x 9 x 20	269.00
210-540WG	Tire 24x8-14 20 Ply Severe Duty	444.00
210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	718.00
210-175WG	Forklift New, 6.5 x 10 - 12 ply rated on 2 pcs 5 bolt rim	393.00
210-175FWG	Foam Filled Forklift Tire 6.5 x 10 - 12 ply on 2 pce 5 bolt rim	693.00

Assembly

Net