

SAVIN IM C2000 IM C2500

Copier
 Printer
 Facsimile
 Scanner



11" x 17" Multifunction Color

Take advantage of technology that scales and flexes as your business needs do. Be more productive and efficient with the SAVIN IM C2000/C2500 range of 11" x 17" color devices.

It's time to:

- Print speeds of 20 - 25 ppm.
- Easy-to-use 10.1" Smart Operation Panel with intuitive menu.
- Mobile connectivity options — including NFC, AirPrint® or Mopria.
- Increased uptime and performance — with Intelligent Support.

Access a range of productivity features and upgrades — such as scanning directly to your email or dedicated folders on your network and ensure you have the latest security enhancements and mobile device connectivity options. Our Intelligent Devices are designed to do more as and when your business needs to do more, using technology that's scalable, secure, sustainable and simple.

Get more from your Intelligent Devices:

- Tailor settings to individual users — for quick access to apps used most often.
- Work more efficiently — with expanded paper tray capacity.
- Automatic firmware upgrades — providing maximum security.

SAVIN Intelligent Devices remain current and relevant no matter what your workplace requires. This way, you have ready and easy access to new functionality, when needed. Environmentally-friendly low TEC (Typical Electricity Consumption) values deliver reduced energy consumption and cut running costs, while Intelligent Support features such as Predictive Maintenance mean that device performance is monitored and any fixes resolved swiftly — minimizing the impact on your workplace.

All Intelligent Devices provide:

- Quick access to Web Help Tools via Intelligent Support.
- A consistent user interface and experience across your Savin fleet.
- Easy integration with third party solutions.
- Regular functionality upgrade releases to do more, smarter and faster.

Ready to take a swipe at a faster way to work? Our range of Intelligent Devices come fitted with a 10.1" Smart Operation Panel designed to enhance your productivity, mobility and environmental commitment. Experience a user interface that offers fast and simple navigation with the ability to customize the layout to best suit your needs — even by adding your own company branding. Access device features, move between jobs and tasks quickly and conveniently enable teams to work smarter.



SAVIN IM C2000/IM C2500

MAIN SPECIFICATIONS

| | IM C2000 | IM C2500 |
|--------------------------------|---|--|
| GENERAL | | |
| Warm-up time | | 21 seconds |
| First output speed: B/W | | 5.1 seconds |
| First output speed: full color | | 7.4 seconds |
| Continuous output speed | 20 ppm | 25 ppm |
| Memory: standard | | 2 GB |
| Memory: maximum | | 4 GB |
| HDD: standard | | 320 GB |
| HDD: maximum | | 320 GB |
| ARDF capacity | | 100 sheets |
| Weight | 200.6 lbs / 91 kg | 200.6 lbs / 91 kg |
| Dimensions: W x D x H | | 587 x 685 x 913 mm, 23.1" x 27.0" x 35.9" |
| Power source | | 120V - 127V 60Hz |
| COPIER (STANDARD) | | |
| Multiple copying | Up to 999 copies | |
| Resolution | 600 dpi | |
| Zoom | From 25% to 400% in 1% steps | |
| PRINTER (STANDARD) | | |
| CPU | Intel Apollo Lake 1.3GHz | |
| Printer language: standard | PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation) | |
| Printer language: option | Genuine Adobe® PostScript® 3™, PDF Direct from Adobe® | |
| Print resolution | Up to 1,200 x 1,200 dpi | |
| Network interface: standard | Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B | |
| Network interface: option | Wireless LAN (IEEE 802.11a/b/g/n), Additional NIC (2nd port) | |
| Mobile printing capability | Apple AirPrint®, Mopria, Google Cloud Print, NFC, Ricoh Smart Device Connector | |
| Windows® environments | Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012R2, Windows® Server 2016 | |
| Mac OS environments | Macintosh OS X v10.11 or later | |
| UNIX environments | UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX | |
| SAP® environments | SAP® R/3®, S/4® | |
| Other supported environments | IBM iSeries AS/400 using OS/400 Host Print Transform | |
| SCANNER (STANDARD) | | |
| Scanning speed | 80 ipm (simplex) | |
| Resolution: maximum | Up to 1,200 dpi | |
| Compression method | TIFF (MH, MR, MMR, JBIG2), Grayscale | |
| File formats | Single Page: TIFF, JPEG, PDF, PDF/A, High Compression PDF, encryption PDF, OCR* Multi Page: TIFF, PDF (Default), PDF/A, High Compression PDF, encryption PDF, OCR* * Requires optional OCR Unit Type M13 | |
| Scan modes | E-mail, Folder, USB, SD Card | |
| FACSIMILE (OPTIONAL) | | |
| Circuit | PSTN, PBX | |
| Transmission speed | 2 seconds (200 x 100 dpi, JBIG, ITUT #1 chart TTI off, memory transmission) | |
| Modem speed: maximum | 33.6 Kbps | |
| Resolution: standard | 8 x 3.85 line/mm, 200 x 100 dpi | |
| Resolution: option | 16 x 15.4 line/mm, 400 x 400 dpi | |
| Compression method | MH, MR, MMR, JBIG | |
| Scanning speed | 68 spm | |
| Memory: standard | 4 MB (320 pages) | |
| Memory: maximum | 60 MB (4,800 pages) | |
| PAPER HANDLING | | |
| Recommended paper size | Tray 1: 8-1/2" x 11" (A4) Tray 2: 5-1/2" x 8" - 12" x 18" (SRA3, A3 - A6, B4 - B6), Envelopes Bypass tray: Up to 12" x 18", Envelopes, Custom Sizes [Width: 3.5" - 12.6" (90 - 320 mm), Length: 5.8" - 49.6" (148 - 1260 mm)] | |
| Paper input: standard | 1,200 sheets | |
| Paper input: maximum | 2,300 sheets | |
| Paper output: standard | 500 sheets 8.5" x 11" (A4) or smaller; 250 sheets (B4) or larger | |
| Paper output: maximum | 1,625 sheets | |
| Paper weight | Trays: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m²) Bypass: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m²) Duplex: 14 - 45 lb. Bond/142 lb. Index (52 - 169 g/m²) | |
| Paper types | Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-printed, Bond, Coated, Envelope, Label, OHP, Gloss | |

SAVIN IM C2000/IM C2500

MAIN SPECIFICATIONS

| | IM C2000 | IM C2500 |
|---|--|----------|
| ECOLOGY | | |
| Power consumption: maximum | Less than 1,584 W | |
| Power consumption operation: B/W | 422.5 W | 454.7 W |
| Power consumption operation: full color | 462.3 W | 498.5 W |
| Power consumption: ready | 45.2 W | |
| Power consumption: sleep | 0.54 W | |
| TEC ¹ | 0.24 kWh | 0.29 kWh |
| ENERGY STAR® | Certified | |
| EPEAT® | Gold Rated* | |
| | * EPEAT Gold rating is applicable only in the USA. | |

OUTPUT TRAYS AND FINISHER OPTIONS

| | |
|---------------------------------------|---|
| 1 x 550-sheet Paper Tray (PB3270) | Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m ²) |
| 2 x 550-sheet Paper Tray (PB3300) | Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m ²) |
| 1,000-sheet Booklet Finisher (SR3270) | Paper size: Proof Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Shift Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Booklet Tray: 8.5" x 11" to 12" x 18" (A4 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²); Stack capacity: 1,000 sheets; Staple capacity: 50 sheets; Staple paper size: Normal Staple: 8.5" x 11" to 12x18" (A4 - A3); Saddle Stitch: 8.5" x 11" to 12" x 18" (A4 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m ²); Staple positions: Top, Bottom, 2 staples, Booklet |
| 250-sheet Internal Finisher (SR3300) | Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²), Stack capacity: 250 sheets, Staple capacity: 5 sheets, Staple paper size: 7.25" x 10.5" to 11" x 17" (B5 - A3), Staple paper weight: 17 - 21 lb. Bond (64 - 80 g/m ²), Staple positions: Top |
| 500-sheet Internal Finisher (SR3250) | Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²); Stack capacity: 500 sheets; Staple capacity: 50 sheets; Staple paper size: 7.25" x 10.5" to 11" x 17" (B5 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m ²); Staple positions: Top, Bottom, 2 staples |
| Internal Shift Tray (SH3080) | Tray capacity: 250 sheets with 80g/m ² paper (A4, LT or smaller), 125 sheets with 80g/m ² paper (B4, LG or larger), Paper size: 12.60" x 23.62" or smaller, Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²) |
| One-bin Tray (BN3130) | Tray capacity: 125 sheets, Paper size: 5.5" x 8.5" to 12" x 18" (A5 - A3), Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²) |

OTHER OPTIONS

Fax Option Type M37, G3 Interface Unit Type M37, Memory Unit Type M37 4GB, Cabinet Type F, Caster Table Type M3, VM CARD Type M37, Punch units (PU3070, PU3080), PostScript3 Unit Type M37, IEEE 802.11a/g/n Interface Unit Type M19, Device Server Option Type M37, File Format Converter Type M19, OCR Unit Type M13, Imageable Area Extension Unit Type M19, External Keyboard Bracket Type M19, Optional Counter Interface Unit Type M12, Key Counter Bracket Type M3, NFC Card Reader Type M37, Smart Card Reader Built-in Unit Type M37, ESP XG-PCS-15D, External USB Keyboard (No Bracket), FAX Memory Unit Type M19 64MB, Bridge Unit BU 3090, Banner Paper Guide Tray Type M19

CONSUMABLES

| | |
|--|---------------|
| Toner: black | 16,500 prints |
| Toner: cyan/magenta/yellow | 10,500 prints |
| Consumable yield measuring method based on A4, 5% coverage | |

¹ TEC value is measured based on the ENERGY STAR Ver. 3.0 test method.

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Savin parts and supplies.

Some features may require additional options and/or charges.

Ricoh USA, Inc.

300 Eagleview Boulevard
Exton, PA 19341



1-877-472-8460



www.savin.com



Ricoh USA, Inc., 300 Eagleview Boulevard, Exton, PA 19341, 1-877-472-8460
©2019 Ricoh USA, Inc. All rights reserved. Savin® and the Savin logo are registered trademarks of Ricoh USA, Inc. Ricoh® and the Ricoh Logo are registered trademarks of Ricoh Company Ltd. All other trademarks are the property of their respective owners. Savin products and services are offered by Ricoh USA, Inc. and its affiliates. The content of this document, and the appearance, features and specifications of Savin products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Savin products and services are as set forth in the express warranty statements accompanying them